




Collared Eyebolt to BS4278 Part 1 1984 (Tested and Certified) Specification Sheet



- * Available in Zinc Plated
- Safe Working Load based on vertical Lift

A (mm)	B (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	SWL Tonne	Weight (kgs)	Product Code
6	22	7	15	9	20	18	0.10	0.07	MCE06
8	22	7	15	9	20	18	0.15	0.07	MCE08
10	22	7	15	9	20	18	0.33	0.07	MCE10
12	22	7	15	9	20	18	0.40	0.07	MCE12*
14	31	10	20	13	26	24	0.50	0.08	MCE14
16	29	10	20	12	26	23	0.80	0.16	MCE16*
18	36	12	24	14	32	28	1.00	0.28	MCE18
20	40	14	27	16	36	32	1.60	0.44	MCE20*
22	45	15	30	18	40	35	1.60	0.56	MCE22
24	52	17	35	21	46	40	2.50	0.84	MCE24*
27	52	17	35	21	46	45	2.50	1.41	MCE27
30	65	22	44	26	58	51	4.00	1.66	MCE30*
33	72	24	48	28	64	56	5.00	2.24	MCE33
36	81	27	54	32	72	63	6.30	3.17	MCE36*
39	90	30	60	36	80	70	6.30	3.92	MCE39
42	101	34	68	40	90	79	8.00	6.00	MCE42
45	101	34	68	40	90	79	8.00	6.00	MCE45
48	101	34	68	40	90	79	10.00	6.00	MCE48
52	115	38	76	46	102	89	12.50	9.00	MCE52
56	128	40	86	51	114	100	16.00	13.00	MCE56
64	144	62	96	58	128	112	20.00	17.50	MCE64